| Fast drying by efficient air flow blower | Hygienic cleansing by UV-C light for your health | Health improving blue light | Easy handling by simple touch on tactile buttons | Drying, cleansing and charging by Dual-USB standard | Gravity sensor for safety shut-off | Automatic turn-off after 2 hours | All features controlled by microprocessor | Highest product quality with 2 year warranty | Energy-efficient, gentle and absolutely safe |

PRODUCT DESCRIPTION

The dry-cap uv 2® is an electronic drying cap with Dual-USB connection and UV-C light for hygienic cleansing.
It dries and cares for all types of rechargeable hearing aids, RIC receivers, tinnitus masks, ear moulds and hearing protection. Many other products can be hygienically cleansed too.

IDENTIFICATION

Product name:	dry-cap uv 2®
SKU:	90600000

TECHNICAL DATA

Drying:	Fast drying due to efficient air blower
Button:	Left button for Dry&Clean mode: 2 min. UV-C light + 116 min. drying + 2 min. UV-C light
	Right button for Clean Mode: Cleansing by 2 min. UV-C light
Switch-off:	Automatic after 2 h / 2 min.
Disinfection:	By UV-C light with 253.7 nm wavelength
	Up to 99.9% of all common germs and bacteria are effectively eliminated
	UV-C intensity max. 4,900 µW/cm², coverage area at 10 cm ~1,200 µW/cm²
Operation:	5V USB base via supplied USB switching power supply or USB 2.0 interface
Safety:	Input voltage monitoring at < 4 V and > 6 V
	Automatic safety shutdown on movement by 3G sensor
Power consumption:	Average power 1 W
	Maximum power (UV-C) 3 W
	Stand-by power < 0.1 W

PACKAGING CONTENT

dry-cap uv 2®
Dual-USB power supply
USB-cable 1.0 m
Cleaning cloth
Instruction manual

SWITCHING POWER SUPPLY

Electronic Dual-USB switching power supply (class VI)
Input: 100-240 V, AC 50/60 Hz
Output: 5 V, 2 A, DC
Type: EU / UK / US / JP / AUS available

WARRANTY

2 Years from delivery

MARKING

CE

DIMENSIONS, WEIGHT AND EAN

			EAN
Unit:	120 mm x 120 mm x 120 mm (L x W x H)	315 g	
1 Unit carton:	130 mm x 130 mm x 130 mm (L x W x H)	441 g	42 6027701 814 6
10 Unit carton:	675 mm x 275 mm x 153 mm (L x W x H)	5.100 g	42 6027701 815 3
20 Unit carton:	695 mm x 295 mm x 342 mm (L x W x H)	6.000 g	42 6027701 816 0